



ANTIFREEZE COOLANT PRE-MIX

50/50 ANTICONGELANTE/ REFRIGERANTE PREDILUIDO

IF YOU'RE A LEXUS, TOYOTA OR SCION OWNER, YOU'VE FOUND YOUR MATCH WITH OEM EXTENDED LIFE RED.

Meeting or exceeding these particular vehicle specifications, MOTOR STAR RED Antifreeze/Coolant provides excellent high temperature aluminum protection and extended protection against rust, corrosion and pitting caused by cavitation for all coolant system metals.

*When added as an initial fill and properly maintained in accordance with engine manufacturer's maintenance recommendation, MOTOR STAR RED provides superior performance for these automotive or light duty vehicles requiring an OAT engine coolant.

APPLICATION

Asian automotive and light duty vehicles requiring an OAT engine coolant.

RECOMMENDED CHANGE INTERVAL

150,000 miles* or 5 years of service protection.

VEHICLE MAKES

Lexus, Toyota, Scion

COMPATIBILITY

For best results, do not mix with conventional high pH, borate or silicate based coolants.

FORMULATION

Ethylene glycol based. Silicate, borate, nitrite and amine free.

PERFORMANCE FEATURE

Aluminum Compatible

PRODUCT COLOR

Red

PRODUCT OPTIONS

Concentrate and 50/50 Pre-diluted

SPECIFICATION/PERFORMANCE LEVEL

ASTM D3306 JIS K2234

ANTIFREEZE/DE-IONIZED WATER DILUTION CHART

PROTECTION AGAINST FREEZING (°F)	-34	-61	-83
VOLUME % ANTIFREEZE	50	60	70
VOLUME % DE-IONIZED WATER	50	40	30
**PROTECTION AGAINST BOIL-OVER (°F)	264	269	276

**WITH A 100 KILOPASCALS (15 PSI) RADIATOR CAP IN GOOD CONDITION

Never use 100% coolant in concentrated form. A 50% dilution (i.e. when mixed with an equal volume of high quality soft, de-ionized or distilled water) is generally recommended for the best balance of protection against freezing, corrosion and summer boil over. For increased freeze protection in extremely cold areas, a 60% volume concentration can be used. Concentrations of greater than 70% by volume are not recommended.

TYPICAL PRODUCT PROPERTIES

CHARACTERISTIC	PERFORMANCE	TEST METHOD
pH	7.5–8.6	ASTM D1287
Specific gravity ^b	1.065–1.080	ASTM D1122
Freeze point (°C/°F)	-37/-34	ASTM D1177
Foam volume (ml)	150 max.	ASTM D1881
Foam break time (second)	5 max.	ASTM D1881
Reserve Alkalinity (ml)	1.5 max.	ASTM D1121
Chloride (ppm)	25 max.	ASTM D3634
Color	Red	
Glycol Content (wt.%)	47 min.	
Inhibitors and Water Content (wt.%)	53 max.	
Silicon (ppm)	< 10	ASTM D6130
Boron (ppm)	< 10	
Nitrite (ppm)	< 10	

Values shown are for 50-50 pre-diluted coolant. ^b Measured at 15.6°C/60°F



-34.6°F
ANTIFREEZE
PROTECTION

+262°F
ANTI BOIL
PROTECTION

100%
ANTI CORROSION
PROTECTION